

Perfect Binder

Binder 1.1



NEW Perfect binder WITH FULL AUTOMATIC FORMAT CHANGE

Once fitted the book block into the clamp , Binder 1.1. shall automatically and in a few seconds adjust the side gluing and the double creasing of the automatic cover feeder.

Thus it's possible to bind a different book from an another one without making any adjustment

- automatic calculator which calculates the thickness of the dox. in the clamp and
- controls the creasing and side gluing axes.
- Automatic creasing adjustment relating to the thickness of the document
- Automatic adjustment of the cover position in relation to the first folding
- automatic pick-up of the covers by a suction cover feeder with 8 adjustable suckers and - - - air blower (max. size 650 x 380 – min. size 220 x 110)
- Side gluing relating to the automatic creasing and to the thickness of the dox.
- Automatic position of the covers on the feeder
- Anti-glue globule electronic device before the stop
- Automatic outlet of bound dox.
- Automatic screen touch control
- Automatic starting cycle device with timer and infrared cell control

Technical Data	Max. length of the spine 380 mm.
	Thickness of the book block from 2 sheets to 50 mm without adjustment
	Gluing heat control from 120° to 200°
	Low heating standby to avoid the alteration of the glue
	Milling and creasing from 0 to 40 mm.
	easy programming by the means of the “touch screen”
	Speed : 600 books/hour
	Dimension/weight : length 210 c m. – width 95 cm. – height 135 cm. , 700 kg.